



Model

WK2

Maximum pipe diameter

1½ +

Flow Rate . Flow rate is immaterial as far as Aqua-Rex is concerned. The greater the flow, the more effective the units tend to be.

Product Data

○ Aerial Length	6q6+
○ Aerial Number	4
○ Minimum aerial turns	12 Turns
○ Frequency range	1 . 10 kHz
○ Peak to peak output voltage	82 V
○ Power supply required	120 V
○ Input current	0.03 A
○ Power consumption	1 W
○ Transformer output	9 V. ac
○ Power cable length	5q
○ Dimensions	8+x 6+x 2+
○ Weight	2.2lb
○ Ambient temperature	160°F
○ Humidity non-condensing	80 %
○ Self-diagnostic guard chip	Yes
○ BMS output	No

Self-Diagnostic “Guard Chip” . Every computer system is prone to malfunction, especially if there is a sudden variation in the power supply, which can jam the program. Most systems have to be reset by manual re-booting. Aqua-Rex units overcome this problem by an additional %Guard Chip+program, which monitors the performance of the main program and resets the system automatically if it detects a variation or system failure. There is no need for manual resetting after power outage.

Maintenance . Once installed, the WK2 requires no maintenance.

Lifecycle costs . Running costs are less than \$30.00 per annum. The design life is in excess of 25 years with a 5-year manufacturer’s warranty.

UPC - 5031476000121



Aqua-Rex LLC
t 1-877 640 2170
f 702 256 2175
e sales@aquar-ex.com
3301 Spring Mountain Road
Suite 18
Las Vegas, NV 89102